

MAST MR51 Series Low Frequency Absorbers

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PRODUCT CODE:	MAST MR51 Series Low Frequency Absorbers All MAST PNs leading w/ MR51
MANUFACTURER:	MAST Technologies
ADDRESS:	6370 Nancy Ridge Dr., Suite 103
	San Diego, CA 92121-3212
Emergency Phone:	(858)452-1700 (regular 8-hour line)
	San Diego, CA
Information Phone:	(858)452-1700
	San Diego, CA
Fax Line:	(858)452-1702
	San Diego, CA
Issue Date:	08/01/2013
Supersedes Date:	03/31/2011
Product Use:	Magnetic powder loaded low frequency absorber.

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %
Metal Alloy Powder		70-90%
Acrylic Rubber	67254-76-6	1-10%
Metal Hydroxides	1309-48-4	10-20%

Notes: See additional exposure information in Section 8, below.

SECTION 3: HAZARDS IDENTIFICATION

NFPA Rating:	Health: 2, Flammability: 1, Reactivity: 0
HMIS Classification:	Health: 2, Flammability: 1, Reactivity: 0, Protection: See PPE Section 8.

EMERGENCY OVERVIEW:

Specific Physical Form:Solid sheet elastomerOdor, Color, Grade:Metallic gray with a characteristic rubber odorGeneral Physical Form:Solid

Immediate health, physical, and environmental hazards: Dust from this product may be harmful if inhaled. Abrasion of particles may cause eye, skin, and respiratory tract irritation. Ingestion may cause gastric disturbances. High-heat processing may liberate toxic gases.

POTENTIAL HEALTH EFFECTS:

Eye Contact: Contact with dust may cause irritation to the eyes. Symptoms may include redness, watering, itching, or a burning sensation in the eyes.

Skin Contact: Contact with dust does not generally cause skin irritation.

Inhalation: High concentrations of airborne dust may irritate the respiratory tract, including the nose, throat, and lungs. Symptoms may include coughing, nausea, headaches, or dizziness.

Ingestion: Ingestion may cause irritation to the gastrointestinal tract but is unlikely to occur in industrial or commercial use.

Chronic: Long-term inhalation of metallic dust particles results in siderosis, a benign pneumoconiosis.

SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water. Remove contact lenses. Flush with water for at least 15 minutes while occasionally lifting lower and upper eyelids. If irritation persists seek medical attention.

Skin Contact: Wash material from the skin thoroughly with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air and rest in half-upright position. If breathing is difficult administer oxygen. Never give anything by mouth to an unconscious person. Get medical attention if symptoms develop.

Ingestion: If conscious, immediately rinse mouth and give large amounts of water to drink. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Notes to Physician: High heat processing of this product may liberate thermal decomposition gases, which when inhaled can result in polymer fume fever. This condition is characterized by influenza-type symptoms (fever, cough, and malaise), which usually occurs within a few hours and resolves within 48 hours. Following severe exposure the patient should be kept under medical surveillance for at least 48 hours since delayed pulmonary edema may develop.

SECTION 5: FIRE FIGHTING MEASURES

Fire Hazards: Keep away from heat, sparks, open flame, or other ignition sources.

Flash Point:	Not applicable
Autoignition Temperature:	Not applicable
Flammable Limits in Air (% by volume) – LEL:	Not applicable
Flammable Limits in Air (% by volume) – UEL:	Not applicable
Hazardous Decomposition Products:	See Section 10, below

Extinguishing Media: Use dry chemical, foam, or water spray.

Unsuitable Extinguishing Media: Do not use carbon dioxide (CO₂), if possible.

Special Fire Fighting Procedures: Use self-contained breathing apparatus with full face piece operated in pressure mode and protection for skin. Keep containers cool with water spray, if possible.

SECTION 6: ACCIDENTAL RELEASE MEASURES



Containment Techniques: Solid material is generally not a spill concern; however, dust particles from this material may be applicable to spill containment. Restrict area where spill occurred. Tarp spilled material if outdoors to prevent wind dispersion of particles until clean-up can occur.

Environmental Protection: Do not discharge particles into drains/surface waters/groundwater.

Methods for Cleaning-up: Refer to Section 8, below, for exposure controls. Restrict area and ensure adequate ventilation. Dampen and gently sweep spilled material. Mechanically pick up dampened material and dispose of. Mop or wipe residual from surface using water.

SECTION 7: HANDLING AND STORAGE

Handling: Use proper personal protective equipment when handling (See Section 8, below). Avoid formation and inhalation of dust particles. Do not eat, drink, or smoke when using this product. Use only in a well-ventilated area. Wash thoroughly with soap and water after handling.

Storage: Store in a cool, dry, well-ventilated area away from heat, sparks, open flames, or other sources of ignition.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment (PPE):

Eyes and Face: Use tightly-fitting safety goggles when dust and thermal decomposition gases may be present.

Skin: Use nitrile rubber gloves on hands and wear additional impervious clothing as appropriate to protect skin.

Respiratory: In the event that overexposure cannot be avoided, a full-face respirator with cartridges approved by NIOSH when dust exposure levels are known to be within the unit's capability. Use a positive-pressure, air-supplied respirator if exposure levels are not known or where purifying respirators may not provide adequate protection for thermal decomposition products.

Engineering Controls: Provide local exhaust ventilation in processes to capture dust or thermal decomposition gases at their source.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance:	Solid
Color:	Metallic Gray
Odor:	Characteristic Rubber
Solubility:	Insoluble
Specific Gravity:	3.1
pH:	Not applicable

Boiling Range:	Not applicable
Vapor Density:	Not applicable
Evaporation Rate:	Not applicable
Melting Point:	~120°C (250°F)

SECTION 10: STABILITY AND REACTIVITY DATA

Stability: This product is stable under ordinary conditions of use and storage.

Conditions to Avoid: Avoid storage under heat and by flames, ignition sources and incompatibles. Avoid exposure to temperatures above 250°C.

Incompatibility with Other Materials: Avoid contact or contamination with strong oxidizers and acids and molten alkali metals.

Hazardous Decomposition Products: Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Nitrogen oxides, metal oxides, formaldehyde, silicone dioxide, and carbon oxides.

Hazardous Polymerization: Hazardous polymerization will not occur under normal processing.

SECTION 11: TOXOLOGICAL INFORMATION

Acute Toxicity:	NIOSH – Selected LD50s & LC50s: No data available ACGIH 2000 – Skin Absorption Designation: No data available
Chronic Toxicity:	No data available.
Carcinogenic Status:	IARC Carcinogens: Not listed OSHA – Select Carcinogens: Not listed NTP Eighth Report – Known Carcinogens: Not listed

SECTION 12: ECOLOGICAL INFORMATION

Ecolotoxological Information: Not determined

Chemical Fate Information: Not determined

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of absorbed material in accordance with all federal, state, and local regulations. Dispose of contaminated water in a contained waste treatment system.

SECTION 14: TRANSPORT INFORMATION

DOT Classification: Not regulated

Air Transportation: Not regulated



SECTION 15: REGULATORY INFORMATION

California – Prop 65 Regulations:	Not listed
Clean Air Act Regulations:	Not listed
TSCA (United States):	The ingredients of this product are listed on, or are exempt from listing, on the TSCA inventory.
FDA:	Not listed
USDA:	Not listed
EPA:	Not listed
SECTION 16: OTHER INFORMATION	

Revision Information: Updated to include CAS numbers of ingredients.

Disclaimer: MAST Technologies provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is generated for the purpose of distributing health, safety, and environmental data; it is not a specification sheet nor should any displayed data be construed as a specification. Some of the information presented and conclusions drawn in this document are from sources other than direct test data on the product. Buyer assumes all risk of use, storage, and handling of the product in compliance with applicable federal, state, and local laws and regulations. MAST TECHNOLOGIES MAKES NO WARRANY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. Therefore, MAST Technologies will not be responsible for damages resulting from use of or reliance upon the information contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete, or otherwise misleading.